

CNS304HI 30W ALUMINUM HORN SPEAKER

TECHNICAL DATA SHEET



DESCRIPTION:

The 30W Aluminum Horn Speaker boasts a dual-driver unit structure, ensuring high sensitivity, a wide frequency range, and excellent timbre. Its waterproof certification ensures suitability for outdoor use. The included brackets simplify installation. This speaker's robust aluminum construction and superior sound quality make it ideal for diverse applications requiring clear, reliable audio.

FEATURES:

- Double driver unit structure, with high sensitivity, wide frequency and excellent timbre.
- With waterproof certificate and other certificates and suitable for outdoors.
- Equipped with brackets for installation.

SPECIFICATIONS:

Model	CNS304HI
Rated Power	30W
Rated Voltage 70V 100V	2W-4W-8W-15W
	4W-8W-15W-30W
Sensitivity 1m 1W	105±2 dB
Frequency Response	350 Hz-20, 000 Hz
Max. SPL	120 ±2dB
Dimension (L×W×H)	250mm×250mm×305mm
STIPA (10m)	0.86
Weight	2.5 kg (5.6 lbs)

FEATURES:

1. Fit three 8mm screws in the position where needed to install a speaker;
2. Set the system in those three screws;
3. Connect audio broadcasting wire to the impedance according to the table below

Power Impedance Line Voltage	70V	100V
2.5K	2 W	4 W
1.3K	4 W	8 W
660	8 W	15W
330	15W	30W

Email: Sales@canscorp.com

Add.: Shop No 5-6, Adinath Alpine building, Plot No. 28 A,
Sector 25, Khandeshwar, Navi Mumbai, Maharastra 410209

Web.: WWW.CANSCORP.COM

