

**CNS2107C 1U MULTI-CHANNEL
MEDIA PLAYER WITH CD/USB/FM/BLUETOOTH**

TECHNICAL DATA SHEET



DESCRIPTION:

The CNS2107C is an audio player with CD playback, radio and Bluetooth function. It supports a variety of audio playback, including CD, USB, SD, Bluetooth and radio signals; has full light touch button control and blue LCD display with high brightness to display clear working status of the audios; has one-way Bluetooth output, one-way radio signal output, one-way CD/MP3 audio output, and one-way alternative output of Bluetooth, radio signal or CD/MP3 audios, which meets various requirements in the application scenes.

FEATURES:

- Full light touch button control, blue LCD display with high brightness and clear screen;
- With Mp3 player, built-in USB interface, SD slot, CD disc tray;
- High-end CD suction movement;
- Bluetooth function;
- CD/MP3/MP4/VCD/DVD playback function;
Built-in radio function, digital radio module with high sensitivity;
- With automatic search radio and storage function, AM/FM radio can store 40 stations respectively;
- The radio has a power-off memory function, which can start to work automatically after powered on;

MAG2107C 1U MULTI-CHANNEL MEDIA PLAYER WITH CD/USB/FM/BLUETOOTH

- One-way Bluetooth output, one-way radio signal output, and one-way CD/MP3 audio output;
- One-way alternative output of Bluetooth, radio signal or CD/MP3 audios.
- Support remote control via the IR remote controller.

SPECIFICATIONS:

Model		
Laser Player	Maximum output voltage 1KHz -10dB signal	700±50mV
	Frequency response range	20-19KHz(±1dB)
	THD	0.3%
	Noise	0.02mv
USB	Maximum output voltage	700±50mV
	Frequency response range	20-19KHz(±1dB)
	THD	0.3%
	Noise	0.02mv
SD	Maximum output voltage	700±50mV
	Frequency response range	20-19KHz(±1dB)
	THD	0.3%
	Noise	0.02mv
Bluetooth	Maximum output voltage 1KHz -10dB	1000±100mv
	Frequency response range	20-19KHz(±2dB)
	THD	0.3%
	Noise	0.06mV
	Distance	Best within 10M
Radio function(FM/AM)	Maximum output voltage	1200±100mV
	Amplitude limiting sensitivity	-80dB
	Frequency response range Distortion	40-10KHz(±3dB)
	SNR	0.2%
	Store/Memory function	60dB 40pcs
Protection	Ac fuse	
Power supply	AC110-120V/60Hz/35W	
	AC220-240V/50Hz/35W	
Outer packing dimension(mm)	(L×W×H)534×350×110	
Machined dimension(mm)	(L×W×H)483×210×44	
Gross weight	4.4kg	
Net weight	3.65 kg	

Email: Sales@canscorp.com

Add.: Shop No 5-6, Adinath Alpine building, Plot No. 28 A,
Sector 25, Khandeshwar, Navi Mumbai, Maharashtra 410209

Web.: WWW.CANSCORP.COM

