

CNS1508 WINDOW INTERCOM MICROPHONE SYSTEM

TECHNICAL DATA SHEET



DESCRIPTION:

The DS-1508 window intercom system, crafted from aluminum alloy, features a streamlined design for efficient two-way communication. Equipped with recording and noise reduction functions, it's anti-interference and eliminates echo and howling, ideal for various service counters to enhance communication.

FEATURES:

- Streamlined external extension, circular design, compact size, beautiful in shape. The internal and external connection adopts a 4-pin cable of high-strength tensile, a fully shielded aluminum foil wire, with stronger anti-interference and good sound effect.
- The main unit adopts aluminum alloy shell, high-quality speaker, and super-long metal flexible microphone rod, which is more convenient to realize free two-way intercom with the extension.
- The internal and external volume can be adjusted separately, with unique dynamic channel working indicator light. With one-key mute button, more convenient to control.

- With microcomputer processing circuit and static noise function for echo and howling.
- With a recording jack, which can output internal and external dual-channel mixed sound signals, and can be configured with monitoring.
- With a microphone jack, which can be used to connect other microphones.
- The connection between the extension and the main unit adopts a 3.5mm plug-in plug, which is effective and reliable.

SPECIFICATIONS:

Model	CNS1408
Working Voltage	DC12V
Working Current	500mA
Main Unit Output Power	4W
Extension Output Power	4W
Main Unit Material	Aluminum Alloy
Extension Material	Aluminum Alloy
Main Unit Dimensions	137×102×51mm
Main Unit Microphone Length	50cm
Extension Dimensions	75×22mm
Weight	0.8kg

Email: Sales@canscorp.com

Add.: Shop No 5-6, Adinath Alpine building, Plot No. 28 A,
Sector 25, Khandeshwar, Navi Mumbai, Maharastra 410209

Web.: WWW.CANS CORP.COM

